

DIS - Simultaneous Interpretation Equipment



Mobile Interpreter Booth



The MB 29xx series consist of portable and semi-portable simultaneous interpreter booths. Standard, these booths are designed for 2 persons but they can easily be extended to a 3-or 4 persons booth. Each booth can (optionally) be delivered with a handy flight case or a transport-car.

Two systems are available for ventilation. A permanent one consisting of 2 ventilation units (standard on the MB 29xx) and the other one removable, which enables the connection of an independent (separate) air-conditioning system. Security glass is possible.

For all types it is optional possible to make the cabins according to the demands of the clients (for instance other colours or internal changes).

The series consist of 3 types all according and even better than the latest ISO 4043 norms.

The MB 29xx

The most popular version is MB 2932. It consists of 8 wall-panels (4 window-panels, 3 blind-panels, a door-panel) and 2 roof-panels. The wall-panels are all interchangeable with each other. This means that the door can be fitted in every position. The MB 2952 is the same as the previous one except that it consists of 15 (smaller) panels.

The booth can easily be extended. The booth can be provided with a specially designed flight case, which houses a complete booth or a flight case, which houses even an extended (3-persons) booth.

The build-up time is approx. 5-10 minutes.

How to order

Interpreter Booth:	Order no.:	Accessories:
MB2932	11 10 10003	On request
MB2931	11 10 10004	
MB2952	11 10 10005	
MB2951	11 10 10006	

DIS - Simultaneous
Interpretation
Equipment

MB 2932/31
MB 2952/51



Technical
Specifications -
MB2952

Standard Dimensions:

Inside: 1600 x 1600 x 2000 mm
Outside: 1682 x 1682 x 2041 mm
(incl. roof-elements and std. ventilation)
Table: standard 1600 x 500 mm

Booth consists of 8 panels

Weight: In total - c. 210 kg
(total incl. safety-glass and table)

Sound:

Sound Insulation: better than ISO 4043
- latest version

Standard Colours:

Outside: Grey 871
(light, appr. RAL 7042)

Inside:
Upper wallpanels: White
(table to roof and roof panels)

Lower wallpanels: Dark grey
(floor to table height)

Technical
Specifications -
MB2932

Standard Dimensions:

Inside: 1600 x 1600 x 2000 mm
Outside: 1682 x 1682 x 2041 mm
(incl. roof-elements and std. ventilation)
Table: standard 1600 x 500 mm

Booth consists of 15 panels

Weight: In total - c. 210 kg
(total incl. safety-glass and table)

Sound:

Sound Insulation: better than ISO 4043
- latest version

Standard Colours:

Outside: Grey 871
(light, appr. RAL 7042)

Inside:
Upper wallpanels: White
(table to roof and roof panels)

Lower wallpanels: Dark grey
(floor to table height)

Options to
MB2932/52

Extension set (2931 - 2951):

Inside: 2400 x 1600 x 2000 mm
Including: Window panel, blindpanel,
roof element, table extension.

Table: in one piece for 2400 x 1600
mm cabin

Flightcase: for 1600 x 1600 mm booth

Flightcase: for 2400 x 1600 mm booth

Boothcar "easy drive"

Ventilation System A or B

Plexi glass windows